

CERTIFICATE OF VERIFICATION

Applicant	Gatso USA Inc. 900 Cummings Ctr 222T 01915 Beverly MA, USA
Equipment	T-Series
Manufacturer	Sensys Gatso Group
Type	RT4
Serial number	201504002936
Verification method	The above stated equipment is verified according the SGG instruction: VI_48-05_RT4_Verification
Date of verification	17 November 2017
Due date of verification	16 November 2018
Results	The verification complies to the specifications as described in the stated verification method. See for detailed results the verification report attached to this certificate
Traceability	The verification is executed with calibrated measurement instruments which are traceable to the (inter)national standards of the country of origin. Sensys Gatso measurement instruments are controlled and calibrated according the applicable ISO 9001 procedure O-05.00 Control of measurement instruments.
Haarlem	17 November 2017 Signed for and behalf of Sensys Gatso E. Hoffman  Quality Assurance Officer

VI-48-05 RT4 verification results

Manufacturer: Galiso
Type: RT4
Serial number: 201504002936
Power supply: 12VDC
Measuring range: 20 - 250 km/h (12.5 - 156.2 mph)
Operating temperature range: -20°C - +55°C (-4°F - +131°F)

Verification type: Initial Periodic
Verification date: 17-11-2017
Executed by: S van Leeuwen

Measurement instruments
 Vehicle simulator hardware
 Frequency counter
 PXI + PCIepress MXI + NI 5783
 Tektronik MCA3027

Part	Version	Checksum
RT4_CPU1	2.6.1	0023E03946C180FE242BE32E808BF8A
RT4_CPU2	2.6.1	EC069AE8521267B9F7EB3EF69C82ECB9
RT4_FPGA	14.6.0	13A2A6DAD9B8ACC6E156829478CDB4DB5

Examination results:

Simulated speed	Direction	+20°C (68°F)									Measured values								
		Lane 1			Lane 2			Lane 3			Lane 1			Lane 2			Lane 3		
km/h (mph)		km/h	mph	km/h	mph	km/h	mph	km/h	mph	km/h	mph	km/h	mph	km/h	mph	km/h	mph	km/h	mph
22 (13.7)	Receding	22	13.7	22	13.7	22	13.7	22	13.7	22	13.7	22	13.7	22	13.7	22	13.7	22	13.7
50 (31.1)	Receding	50.1	31.1	50.2	31.2	50.2	31.2	50.2	31.2	50.2	31.2	50.2	31.2	50.2	31.2	50.2	31.2	50.2	31.2
100 (62.1)	Receding	100.4	62.4	100.4	62.4	100.4	62.4	100.4	62.4	100.4	62.4	100.4	62.4	100.4	62.4	100.4	62.4	100.4	62.4
150 (93.2)	Receding	150.7	93.6	150.7	93.6	150.8	93.7	150.8	93.7	150.8	93.7	150.8	93.7	150.8	93.7	150.8	93.7	150.8	93.7
200 (124.3)	Receding	200.9	124.8	200.9	124.8	201	124.9	201	124.9	201	124.9	201	124.9	201	124.9	201	124.9	201	124.9
247 (153.5)	Receding	248.1	154.2	248.2	154.2	248.4	154.3	248.4	154.3	248.4	154.3	248.4	154.3	248.4	154.3	248.4	154.3	248.4	154.3
-22 (-13.7)	Approaching	-22.3	-13.9	-22.3	-13.9	-22.3	-13.9	-22.3	-13.9	-22.3	-13.9	-22.3	-13.9	-22.3	-13.9	-22.3	-13.9	-22.3	-13.9
-50 (-31.1)	Approaching	-50.4	-31.3	-50.4	-31.3	-50.3	-31.3	-50.3	-31.3	-50.3	-31.3	-50.3	-31.3	-50.3	-31.3	-50.3	-31.3	-50.3	-31.3
-100 (-62.1)	Approaching	-100.3	-62.3	-100.3	-62.3	-100.2	-62.3	-100.2	-62.3	-100.2	-62.3	-100.2	-62.3	-100.2	-62.3	-100.2	-62.3	-100.2	-62.3
-150 (-93.2)	Approaching	-150.6	-93.6	-150.6	-93.6	-150.6	-93.6	-150.6	-93.6	-150.6	-93.6	-150.6	-93.6	-150.6	-93.6	-150.6	-93.6	-150.6	-93.6
-200 (-124.3)	Approaching	-201.2	-125.0	-200.8	-124.8	-200.6	-124.6	-200.6	-124.6	-200.6	-124.6	-200.6	-124.6	-200.6	-124.6	-200.6	-124.6	-200.6	-124.6
-247 (-153.5)	Approaching	-248.1	-154.1	-248.1	-154.2	-248.1	-154.2	-248.1	-154.2	-248.1	-154.2	-248.1	-154.2	-248.1	-154.2	-248.1	-154.2	-248.1	-154.2
		+20°C (68°F)			20°C (68°F)			+55°C (131°F)											
Start Tx Frequency (MHz)		24.023																	
Stop Tx Frequency (MHz)		24.244																	